



Cutler-Hammer

Transformers

Capabilities

Dry-Type Transformers

Product Offering

- VPI, VPE, RESIBLOC®, Cast
- 113 kVA – 25 MVA
- Up to 46 kV, 150 kV BIL primary
- Up to 15 kV secondary

Standards

- ANSI C57.12.01/C57.12.91
- UL® available
- Seismic Zone 4 certification

Industry Applications

- Commercial and institutional
- Industrial users (petrochemical, oil & gas, pulp & paper/forest)
- Utilities



Liquid-Filled Transformers

Product Offering

- Primary and secondary unit substations, power substations
- 112.5 kVA – 20 MVA
- Up to 69 kV primary
- Up to 34.5 kV secondary
- Mineral oil, R-Temp®, silicone or BIOTEMP™

Standards

- Complies with ANSI C57.12.00 and C57.12.90, CSA® – C88
- UL, FM available
- Seismic Zone 4 certification

Industry Applications

- Commercial and institutional
- Industrial users (petrochemical, oil & gas, pulp & paper/forest)
- Utilities



Pad-Mounted Transformers

Product Offering

- Small 75 – 3000 kVA
- Large 3000 – 7500 kVA
- Up to 34.5 kV high voltage
- Up to 5 kV low voltage
- Underground cable fed
- Mineral oil, R-Temp, silicone or BIOTEMP

Standards

- Complies with ANSI C57.12.00 and C57.12.90, CSA – C88
- UL, FM available
- Seismic Zone 4 certification

Industry Applications

- Commercial and institutional
- Industrial users (petrochemical, oil & gas, pulp & paper/forest)
- Utilities



CSA is a registered trademark of the Canadian Standards Association. UL is a federally registered trademark of Underwriters Laboratories Inc. BIOTEMP is a registered trademark of ABB Inc. RESIBLOC is a registered trademark of ABB Inc. R-Temp is a registered trademark of Cooper Power Systems Division and/or Cooper Industries, Inc.

Eaton Electrical Inc.
1000 Cherrington Parkway
Moon Township, PA 15108
United States
tel: 1-800-525-2000
www.EatonElectrical.com

EAT•N

Cutler-Hammer

©2004 Eaton Corporation
All Rights Reserved
Printed in USA
Pub. No. PA09000001E / Z2833
December 2004